

RS Subwoofer Series

Self-Powered Subwoofers RS115 & RS118HP

- ▶ Premium transducers and signature EAW DynO™ dynamic optimization processing
- ▶ 1500 or 2500 watts of Class-D Power Factor Corrected amplification
- ▶ Cardioid pattern can be generated quickly with a button press
- ▶ Ergonomic handles, rugged grille, RoadCoat enclosure, pole cup, and optional casters

OVERVIEW

The RS Series low frequency enclosures deliver EAW signature performance in a portable and lightweight package. Each enclosure in the series is first designed around the latest powerful transducers with enhanced motor strength that optimizes system weight and low frequency output. The RS Series low frequency enclosures include on-board 1500 watt (RS115) and 2500 watt (RS118HP) amplified electronics engineered to meet the demanding performance needs of professionals.

The RS Series features meticulously tuned vented enclosures, as well EAW signature DynO™ algorithms optimize the power transfer from amplifiers to transducers for improved headroom and integrity of sound at maximum output.

Our Resolution software platform is a powerful and easy-to-use simulation tool that accurately predicts the performance of one or multiple RS Series low frequency enclosures within a venue or performance space.



RS118HP



RS115

EAW TECHNOLOGY



DynO™ Dynamic Optimization actively tracks input spectrum and power delivery, continually maximizing output and fidelity at any drive level.

APPLICATIONS

- ▶ Concerts
- ▶ Corporate AV
- ▶ Live Clubs
- ▶ Concert Halls
- ▶ Theaters
- ▶ Auditoriums
- ▶ Houses of Worship
- ▶ Festivals

ACCESSORIES

- ▶ Caster Kit
- ▶ Soft Cover
- ▶ M20 Positive Threaded Wicked Secure Pole

RS Subwoofer Series

TECHNICAL SPECIFICATIONS SELF-POWERED SUBWOOFERS



PERFORMANCE	RS115	RS118HP
Max SPL	132dB (peak, half space)	135dB (peak, half space)
Operating Range	40Hz - 125 Hz	27 Hz - 125 Hz
Nominal Beamwidth		
Horz	360°	
Vert	360°	
CONFIGURATION	RS115	RS118HP
Subsystem	<i>Tranducer</i>	<i>Loading</i>
LF Transducer, Loading	15in Cone, 3 in Voice Coil, Vented	18in Cone, 3 in Voice Coil, Vented
Operating Mode	VLF	
External Signal Processing	DSP with DynO™	
Modes	80 Hz / 110 Hz / Polarity	
ELECTRICAL	RS115	RS118HP
Input Type	Electronically Balanced XLR (stereo)	
Loop Type	Electronically Balanced XLR (stereo)	
Amplifier		
Type	Class D	
Max Output LF / HF (Peak)	1500W	2500W
AC Mains (nominal)		
Connector	IEC Connector	Neutrik PowerCON®
Input	100-120V or 200-240V, 50-60Hz	
PHYSICAL	RS115	RS118HP
Physical/Rigging	Vibration Isolation Feet	
Dimensions (HxWxD)	17.7" x 24.8" x 23.6" (450mm x 630mm x 599mm)	20.5" x 30.0" x 26.8" (521mm x 762mm x 681mm)
Net Weight*	63lb (28kg)	99lb (45kg)
Shipping Weight*	73lb (33kg)	109lb (50kg)

*Preliminary

COMPANION PRODUCTS



RS SERIES LOUDSPEAKERS

- ▶ Leading-edge touring grade transducers
- ▶ EAW Focusing for unmatched clarity and accuracy
- ▶ Rotatable MK inspired horn for EAW signature pattern control
- ▶ Lightweight and durable wooden enclosure with M10 threaded suspension points



LA SERIES LOUDSPEAKERS

- ▶ Leading-edge touring grade transducers
- ▶ Lightweight and durable resonant free enclosure
- ▶ EAW Focusing for unmatched clarity and accuracy
- ▶ Consistent sonic signature even outside of its pattern



One Main Street
Whitinsville, MA 01588
Tel 800 992 5013 / +1 508 234 6158

www.eaw.com

1903_RS_SUB_SPEC

